

POLYFLEX®

PRODUCT DESCRIPTION

Polyflex membranes are premium, polyester reinforced APP modified bitumen roofing products specially designed for heat-welded applications. Constructed with premium Atactic Polypropylene resins, and incorporating superior polyester reinforcing, Polyflex provides an exceptionally durable roofing product which is easy to install and will provide long-term weathering performance.

With a smooth surface and either a polyolefin or sand backing, Polyflex exceeds all minimum ASTM standards for tensile strength, puncture resistance and flexibility.

Polyflex membranes can also be used as flashing membranes in all applicable specifications, in accordance with recommended installation practices.

USES

- Heat-welded or cold-applied base or cap sheet
- Applied directly over an acceptable substrate or as part of a multi-ply system
- New roofing, re-roofing, re-cover and for flashing details

FEATURES AND BENEFITS

- Exceptional weathering characteristics
- Puncture and tear resistant
- Low-temp flexibility, exceptional tensile strength and elongation properties

TECHNICAL DESCRIPTION

TEST METHOD	PROPERTY	TYPICAL VALUE
ASTM D5147	Thickness, typical, mm (mils)	4.0 (160)
ASTM D5147	Peak Load @ 23+/-2C (73.4+/-3.6F), MD and XMD, min, kN/m (lbf/in.)	8.8 (50)
ASTM D5147	Elongation @ 23+/-2C (73.4+/-3.6F), MD and XMD, min (%)	23
ASTM D5147	Tear Strength @ 23+/-2C (73.4+/-3.6F), min, N (lbf)	311 (70)
ASTM 6222	Low Temperature Flexibility, max, C (F)	0 (32)



PRODUCT DATA

Coverage (Approx)..... 100 sq ft
 Weight..... 85 lbs
 Roll Size32'10" x 39 3/8" (10m x 1m)
 Rolls/Pallet.....23

APPLICABLE STANDARDS

- ASTM D 6222 Type I
- Miami Dade Code Compliance
- Factory Mutual Approved
- UL Classified for use in class A, B or C roofs, as listed in the latest UL "Roofing Materials and Systems Directory"
- ICC ESR-2018
- TDI



PRODUCT WARRANTY

Unless otherwise incorporated into or part of a supplemental manufacturer's warranty, Polyglass warrants its product(s) for a period of 10 years against manufacturing defects in its product that directly results in leakage. Warranty coverage is an annually declining pro-rated warranty.



Adds value!

1-800-222-9782

www.polyglass.com

POLYFLEX®

APPLICATION INSTRUCTIONS

Polyflex is intended to be used as a base sheet or inter ply in new or re-roof applications. Polyflex may be applied directly to non-combustible substrates. Polyflex requires the installation of a compatible granulated cap sheet to complete the roofing system.

- Apply over clean, dry, dust and debris-free substrates. Prime concrete decks prior to application with PG 100 Asphalt Primer.
- When re-roofing, remove all prior roofing materials down to a clean debris-free substrate and properly close-off all abandoned roof penetrations.
- Concrete or steel decks shall be designed with proper expansion devices.
- Wood decks shall have all joints blocked and properly supported.
- Ensure the fire rating of the assembly over any combustible substrate.
- Ensure the installation of Polyflex does not prevent the ventilation of existing construction.
- Do not apply over shingles or any granulated surface.
- While installing Polyflex:
 1. Start at the low point of the roof.
 2. Unroll the material and allow to relax in the sun for at least 15 minutes.
 3. Install with traditional torch roofing techniques ensuring proper heating of the roofing material as not to expose the reinforcement.
 4. Do not heat the substrate.
 5. Position successive rolls providing a minimum 6" end lap and 3" side lap. Asphalt bleed out shall be 1/4" to 3/8" on all seams.
 6. Laps shall be rolled with a 6"-wide roller immediately after heat welding.
- Details and flashing may be installed using Polyflex with torch applied techniques. Do not use cold adhesives or hot asphalt. Check project details for proper installation requirements.

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Winter Haven, FL



Adds value!

1-800-222-9782

www.polyglass.com